

View Online at <https://aerobasegroup.com/nsn/4810-01-627-8017>

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

212.0 degrees fahrenheit single response

Minimum Operating Temp:

-40.0 degrees fahrenheit

End Application:

Sentinel class fast response cutter b (frc-b)

Connection Style:

Plain (screw-in cartridge) 1st end

Valve Operation Method:

Solenoid

Connection Type:

Threaded cartridge 1st end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

12 1st end

Maximum Operating Pressure:

5000.0 pounds per square inch single response

Thread Size:

1.312 inches 1st end

Voltage In Volts And Current Type:

24.0 dc

Product Name:

Solenoid valve, cartridge 2-way, 2 position

Special Features:

Cms data id 7357 pccn se0366 plisn a040; next higher assembly steering system p/n 3892-1000

Material:

Steel

Style Designator:

Screw-in cartridge

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0