

View Online at <https://aerobasegroup.com/nsn/4810-01-631-2836>

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Maximum Operating Temp:

100.0 degrees celsius 1st response

Minimum Operating Temp:

-30.0 degrees celsius

Connection Style:

Plain (screw-in cartridge) 1st end

Valve Operation Method:

Solenoid

Connection Type:

Threaded cartridge 1st end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

12 1st end

Maximum Operating Pressure:

5000.0 pounds per square inch 1st response

Thread Size:

1.312 inches 1st end

Voltage In Volts And Current Type:

24.0 dc

Product Name:

Solenoid valve, 2-way, poppet type

Special Features:

Detente override; super coil (19 watts); din plug face connector; for use with mineral-based or synthetic with lubricating properties

Material:

Steel body

Material Specification:

Steel mfr ref single material response body

Media For Which Designed:

Oil, hydraulic single response

Style Designator:

Screw-in cartridge

Thread Series Designator:

Unf 1st end

Furnished Items And Quantity:

1 electrical connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0