

View Online at <https://aerobasegroup.com/nsn/4810-01-631-2837>

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Spool

Maximum Operating Temp:

93.3 degrees celsius single response

Minimum Operating Temp:

-40.0 degrees celsius

Connection Style:

Plain (screw-in cartridge) 1st end

Valve Operation Method:

Solenoid

Connection Type:

Threaded cartridge 1st end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

14 1st end

Maximum Operating Pressure:

5000.0 pounds per square inch single response

Thread Size:

0.875 inches 1st end

Voltage In Volts And Current Type:

24.0 dc

Product Name:

Solenoid valve, 3-position, 4-way floating center spool valve

Special Features:

Nitrile seals; manual push-pull override; super coil (19 watts); din plug face connector; for use with mineral-based or synthetic oil with lubricating properties

Material:

Steel body

Material Specification:

Steel mfr ref single material response body

Media For Which Designed:

Oil, hydraulic single response

Style Designator:

Screw-in cartridge

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0