

View Online at <https://aerobasegroup.com/nsn/4810-01-631-3455>

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Spool

**Maximum Operating Temp:**

100.0 degrees celsius single response

**Minimum Operating Temp:**

-30.0 degrees celsius

**Connection Style:**

Plain (screw-in cartridge) 1st end

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded cartridge 1st end

**Mounting Position:**

Horizontal or vertical

**Thready Qty Per Inch (tpi):**

16 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.75 inches 1st end

**Voltage In Volts And Current Type:**

24.0 dc

**Product Name:**

Solenoid valve, spool type, 3-way 2 position

**Special Features:**

Screw type manual override; super coil (19 watts); din plug face connector; nitrile seals

**Material:**

Steel body

**Material Specification:**

Steel mfr ref single material response body

**Media For Which Designed:**

Oil, hydraulic single response

**Surface Treatment:**

Zinc

**Style Designator:**

Screw-in cartridge

**Thread Series Designator:**

Unf 1st end

**Furnished Items And Quantity:**

1 electrical connector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0