NSN 4820-00-001-6159

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-001-6159

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Connection Style:
Flared (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Facility:
Bulkhead
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 all ends
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.438 inches all ends
Seat Angle:
37.0 degrees all ends
Outside Diameter Tube Accommodated:
0.250 inches all ends
Material:
Steel flow control device
Material Specification:
Qq-s-763 class 4400 federal specification single material response flow control device
Media For Which Designed:
Oil, hydraulic single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unf 1st end

NSN 4820-00-001-6159

Check Valve - Page 2 of 2



Shelf L	ife:
---------	------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.