## NSN 4820-00-003-5561

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-003-5561 **Thread Direction:** Right-hand 1st end **Flow Control Device: Poppet Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Minimum Operating Temp:** -40.0 degrees fahrenheit **Connection Style:** Plain, optional en (pipe) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe 1st end **Features Provided:** Bonnet packing and pressure tight outlet side **Adjustable Pressure Range:** +40.0/+125.0 pounds per square inch **Maximum Operating Pressure:** 125.0 pounds per square inch single response **Thread Size:** 0.375 inches 1st end Material: Rubber synthetic seat Media For Which Designed: Fuel/oil, hydrocarbon 2nd response **Style Designator:** Angle **Thread Series Designator:** Npt 1st end **Furnished Items And Quantity:** 1 cap Shelf Life: N/a

Unit Of Measure:

## NSN 4820-00-003-5561

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0