## NSN 4820-00-003-5561

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-003-5561

Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Minimum Operating Temp:
-40.0 degrees fahrenheit
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Bonnet packing and pressure tight outlet side
Adjustable Pressure Range:
+40.0/+125.0 pounds per square inch
Maximum Operating Pressure:
125.0 pounds per square inch single response
Thread Size:
0.375 inches 1st end
Material:
Rubber synthetic seat
Media For Which Designed:
Fuel/oil, hydrocarbon 2nd response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Furnished Items And Quantity:
1 сар
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 4820-00-003-5561

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

