## NSN 4820-00-003-9553

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-003-9553 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Unable To Decode:** Between 0.099 inches and unable to decode Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Connection Style:** Flareless 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 2nd end **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 18 2nd end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end Seat Angle: 12.0 degrees 2nd end **Outside Diameter Tube Accommodated:** 0.500 inches 1st end Material: Stainless steel seat Media For Which Designed: Oil, hydraulic single response **Style Designator:** Straight thru **Thread Series Designator:** Unjf 1st end Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 4820-00-003-9553

Restrictor Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0