

View Online at <https://aerobasegroup.com/nsn/4820-00-004-6971>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Bonnet Type:**

Inside spring

**Bonnet Attachment Method:**

Integral

**Disk Loading Method:**

Spring

**Renewable Seat Ring Type:**

Pressed-in

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**Connection Style:**

Flared (tube) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 1st end

**Features Provided:**

Bonnet packing and pressure tight outlet side

**Thready Qty Per Inch (tpi):**

16 1st end

**Adjustable Pressure Range:**

+40.0 to 125.0 pounds per square inch

**Maximum Operating Pressure:**

125.0 pounds per square inch single response

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Opening Pressure Setting:**

90.0 pounds per square inch

**Outside Diameter Tube Accommodated:**

0.500 inches 1st end

**Material:**

Stainless steel flow control device

**Media For Which Designed:**

Water-oil-gas single response

**Surface Treatment:**

Anodize

**Style Designator:**

Angle

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0