

View Online at <https://aerobasegroup.com/nsn/4820-00-004-6971>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Connection Style:

Flared (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Features Provided:

Bonnet packing and pressure tight outlet side

Thready Qty Per Inch (tpi):

16 1st end

Adjustable Pressure Range:

+40.0 to 125.0 pounds per square inch

Maximum Operating Pressure:

125.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Opening Pressure Setting:

90.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Material:

Stainless steel flow control device

Media For Which Designed:

Water-oil-gas single response

Surface Treatment:

Anodize

Style Designator:

Angle

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A046b0