## NSN 4820-00-005-4903



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-005-4903 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 225.0 degrees fahrenheit 1st response **Connection Style:** Gasket seal (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Mounting Position:** Horizontal **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 1.062 inches all ends **Outside Diameter Tube Accommodated:** 0.750 inches all ends **Special Features:** Valve cracking pressure 5 psi Material: Steel comp 303 flow control device and steel comp 304 flow control device **Material Specification:** Qq-c-676 military specification single material response body Media For Which Designed: Fuel/oil, hydrocarbon 2nd response **Style Designator:** Straight thru **Thread Series Designator:** Unjf all ends Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 4820-00-005-4903

Check Valve - Page 2 of 2



Fiig:

A530b0

Mil-std (military Standard):

Mil-g-1149 spec.