NSN 4820-00-007-1160

Calibrated Flow Valve - Page 1 of 2

Body Material:



View Online at https://aerobasegroup.com/nsn/4820-00-007-1160

Aluminum alloy
Outside Surface Treatment:
Anodized
Body Style:
Straight thru
Stem Material:
Steel
Media For Which Designed:
Hydraulic oil
First End Connection Type:
Threaded internal pipe
First End Style Designator:
Plain
First End Thread Size And Series/type Designator:
0.750-14 npt
First End Thread Direction:
Right-hand
Second End Relationship With First End:
Identical
Third End Relationship With Preceding Ends:
Identical with first end
Fourth End Relationship With Preceding Ends:
Identical with first end
Seat Material:
Rubber, buna-n
Center To Center Distance:
2.125 inches
Flow Control Device:
Piston, free type
Flow Control Device Material:
Steel
End Connection Quantity:
4
Valve Discharge Flow Rate:
40.0 gallons per minute
Renewable Seat Ring Type:
Pressed-in
Mounting Facility:
Flange
Regulation Type:
Manual, double stage

NSN 4820-00-007-1160

Calibrated Flow Valve - Page 2 of 2



M	an	ııal	Co	ntro	I M	leth	od:
IVI	an	uai	CO	nuo	I IV	eu	ıou.

Screw

Maximum Inlet Pressure Rating:

300.0 pounds per square inch

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100