NSN 4820-00-008-6104



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-008-6104 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Minimum Operating Temp:** -65.0 degrees fahrenheit **Connection Style:** Flared (tube) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 1st end **Features Provided:** Bonnet packing Thready Qty Per Inch (tpi): 18 1st end **Maximum Operating Pressure:** 3345.0 pounds per square inch single response **Thread Size:** 1.125 inches 1st end Seat Angle: 37.0 degrees 1st end Material: Steel comp 440c seat Media For Which Designed: Hydraulic fluid, petroleum base single response **Style Designator:** Angle **Thread Series Designator:**

Unef 1st end

Shelf Life:

N/a

NSN 4820-00-008-6104

Safety Relief Valve - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0