## NSN 4820-00-009-5209

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-009-5209 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 280.0 degrees fahrenheit single response **Minimum Operating Temp:** -40.0 degrees fahrenheit **Connection Style:** Plain (tube) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 1st end **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end **Opening Pressure Setting:** 42.0 pounds per square inch Material: Aluminum alloy 2024 body **Material Specification:** Qq-a-225/6, alloy2024, t4 federal specification single material response seat Media For Which Designed: Hydrogen 5th response **Style Designator:** Straight through w/baffle **Thread Series Designator:** Unif 1st end **Furnished Items And Quantity:** 1 deflector cap Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 4820-00-009-5209

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0