## NSN 4820-00-009-5209

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-009-5209

View Online at https://aerobasegroup.com/nsn/4820-00-009-5209
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
280.0 degrees fahrenheit single response
Minimum Operating Temp:
-40.0 degrees fahrenheit
Connection Style:
Plain (tube) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Opening Pressure Setting:
42.0 pounds per square inch
Material:
Aluminum alloy 2024 body
Material Specification:
Qq-a-225/6, alloy2024, t4 federal specification single material response seat
Media For Which Designed:
Hydrogen 5th response
Style Designator:
Straight through w/baffle
Thread Series Designator:
Unjf 1st end
Furnished Items And Quantity:
1 deflector cap
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 4820-00-009-5209

Safety Relief Valve - Page 2 of 2

**Fiig:** A046b0

