## NSN 4820-00-010-6019

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-010-6019

Pipe Size Accommodated:
0.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
189.0 cubic feet per minute
Maximum Operating Temp:
165.0 degrees fahrenheit single response
Connection Style:
Streamlined with one brazing ring all ends
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Maximum Operating Pressure:
400.0 pounds per square inch single response
Opening Pressure Setting:
55.0 pounds per square inch
Material:
Nickel alloy
Material Specification:
Qq-n-281 federal specification 1st material response seat or qq-n-288 federal specification 2nd material response seat
Media For Which Designed:
Air single response
Style Designator:
Angle
Test Data Document:
81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Furnished Items And Quantity:
2 nut and 2 tailpiece and 1 wrench
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-010-6019

Safety Relief Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A046b0