# NSN 4820-00-011-9620

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-011-9620

Thread Class:

3a all ends

**Thread Direction:** 

Right-hand all ends

# Flow Control Device:

Poppet

# Disk Loading Method:

Spring

### **Connection Style:**

Flared (tube) all ends

# Valve Operation Method:

Automatic

# Connection Type:

Threaded external tube all ends

# **Mounting Position:**

Horizontal or vertical

# Thready Qty Per Inch (tpi):

12 all ends

#### Maximum Operating Pressure:

3000.0 pounds per square inch single response

#### Thread Size:

1.062 inches all ends

### Seat Angle:

37.0 degrees all ends

#### Material:

Steel flow control device

#### **Material Specification:**

Qq-s-763 federal specification single material response flow control device

#### Media For Which Designed:

Hydraulic fluid, mineral base single response

#### Style Designator:

Straight thru

#### **Thread Series Designator:**

Un all ends

Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A530b0

# NSN 4820-00-011-9620

Check Valve - Page 2 of 2

# Mil-std (military Standard):

Mil-s-7720 spec.

