NSN 4820-00-014-1306

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-014-1306 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 12.0 gallons per minute **Maximum Operating Temp:** 600.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side **Adjustable Pressure Range:** +1400.0 to 2300.0 pounds per square inch **Maximum Operating Pressure:** 2300.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Opening Pressure Setting:** 2200.0 pounds per square inch Material: Stainless steel Media For Which Designed: Hydraulic fluid, petroleum base single response **Style Designator:** Straight through note: to be used for valve bodies of one section only. **Thread Series Designator:** Unf all ends Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 4820-00-014-1306

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0