

View Online at <https://aerobasegroup.com/nsn/4820-00-015-6231>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Maximum Operating Temp:

110.0 degrees celsius 2nd response

Connection Style:

External seat for gasket seal (boss) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external boss 1st end

Features Provided:

Valve stem lock shield

Maximum Operating Pressure:

50.0 pounds per square inch single response

Thread Size:

0.562 inches 1st end

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6, alloy2024, t4 federal specification single material response

Media For Which Designed:

Air single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type1, class1 military specification single treatment response

Style Designator:

Straight thru

Test Data Document:

18876-10177850 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.