NSN 4820-00-016-1070



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-016-1070 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 6.0 gallons per minute **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Hydraulic **Connection Type:** Threaded internal boss 1st end **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 16 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end Material: Steel comp 440c seat Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:**

Unjf 1st end Shelf Life: N/a **Unit Of Measure:**

NSN 4820-00-016-1070

Safety Relief Valve - Page 2 of 2



Demi			

Yes - demil/mli

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.