NSN 4820-00-016-1844

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-016-1844

Pipe Size Accommodated:	
0.560 inches 1st end	
Flow Control Device:	
Disk or stem	
Bonnet Type:	
Outside screw-yoke	
Bonnet Attachment Method:	
Bolted	
Connection Style:	
Socket 1st end	
Valve Operation Method:	
Air	
Connection Type:	
Unthreaded internal pipe 1st end	
Valve Size:	
0.250 inches	
Maximum Operating Pressure:	
600.0 pounds per square inch single response	
Material:	
Steel flow control device	
Media For Which Designed:	
Steam single response	
Special Test Features:	
Hydrostatic tests at 2175 psi dorstrength and porosity with disc open, hydrostatic test at 1330 psi for tightness of seat on both sides,	air test
at 100 psi for tightness on seat	
Style Designator:	
Straight thru	
Supplementary Features:	
This item has been reviewed for asbestos material. The current approved sources 13902 has indicated their part number contained	asbestos
prior to 1984. They continue to manufacture the same part number without asbestos material after 1984	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A046b0	