NSN 4820-00-017-7767

View Online at https://aerobasegroup.com/nsn/4820-00-017-7767

Lift-check Valve - Page 1 of 2

Thread Class: 3b 1st end



Thread Direction: Right-hand 1st end Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Threaded **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Flare (tube) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube 1st end **Mounting Facility:** Threaded fastener **Mounting Position:** Horizontal Thready Qty Per Inch (tpi): 12 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 1.500 inches 1st end Seat Angle: 45.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.750 inches 1st end **Special Features:** 90 degrees handle travel ccw for free flow in reverse Material: Stainless steel seat Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Style Designator:** Straight thru

NSN 4820-00-017-7767

Lift-check Valve - Page 2 of 2



Optional flow control device: stem

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0