NSN 4820-00-022-5806

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-022-5806

Body Material: Brass, qq-b-626, alloy 377 Outside Surface Treatment: Lacquer, tt-l-26 and passivated, mil-std-171, finish no. 4.3 Body Style: Angle Furnished Items: Automatic relief valve and bonnet Media For Which Designed: Air and nitrogen First End Connection Type: Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated: 0.250 inches
Outside Surface Treatment: Lacquer, tt-l-26 and passivated, mil-std-171, finish no. 4.3 Body Style: Angle Furnished Items: Automatic relief valve and bonnet Media For Which Designed: Air and nitrogen First End Connection Type: Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated:
Lacquer, tt-l-26 and passivated, mil-std-171, finish no. 4.3 Body Style: Angle Furnished Items: Automatic relief valve and bonnet Media For Which Designed: Air and nitrogen First End Connection Type: Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated:
Body Style: Angle Furnished Items: Automatic relief valve and bonnet Media For Which Designed: Air and nitrogen First End Connection Type: Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated:
Angle Furnished Items: Automatic relief valve and bonnet Media For Which Designed: Air and nitrogen First End Connection Type: Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated:
Furnished Items: Automatic relief valve and bonnet Media For Which Designed: Air and nitrogen First End Connection Type: Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated:
Automatic relief valve and bonnet Media For Which Designed: Air and nitrogen First End Connection Type: Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated:
Media For Which Designed: Air and nitrogen First End Connection Type: Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated:
Air and nitrogen First End Connection Type: Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated:
First End Connection Type: Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated:
Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated:
First End Style Designator: Flared First End Outside Diameter Tube Accommodated:
Flared First End Outside Diameter Tube Accommodated:
First End Outside Diameter Tube Accommodated:
0.250 inches
0.230 inches
First End Thread Size And Series/type Designator:
7/16-20 unf
First End Thread Class:
3a
First End Thread Direction:
Right-hand
Second End Relationship With First End:
Identical
Seat Material:
Any acceptable
First End Seat Angle In Deg:
37.0
Packing Material:
Any acceptable
Flow Control Device:
Diaphragm
Flow Control Device Material:
Any acceptable
End Connection Quantity:
2
Mounting Facility:
Bracket
Regulation Type:
Automatic double stage

Spring

Valve Loading Method:

NSN 4820-00-022-5806

Fluid Pressure Regulating Valve - Page 2 of 2



Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: -Demilitarization: No

Fiig: A21100