NSN 4820-00-024-4744

Check Valve - Page 1 of 2

Flow Control Device:

Disk Loading Method:

Bolt Hole Quantity:

Connection Style:
Beaded (hose) 2nd end

Maximum Operating Temp:

350.0 degrees fahrenheit single response

Poppet

Spring

4 1st end

Width:



View Online at https://aerobasegroup.com/nsn/4820-00-024-4744

1.750 inches all ends
Length:
1.750 inches 1st end
Valve Operation Method:
Automatic
Flange Shape:
Rectangular with holes 1st end
Connection Type:
Unthreaded external hose 2nd end
Mounting Position:
Vertical
Maximum Operating Pressure:
400.0 pounds per square inch single response
Thickness:
0.250 inches 1st end
Bolt Hole Diameter:
0.159 inches 1st end
Center To Center Distance Between Bolt Holes Along Length:
1.038 inches 1st end
Center To Center Distance Between Bolt Holes Along Width:
1.038 inches 1st end
Flange Face Design:
Plain 1st end
Special Features:
Flanged end holes threaded 10-32 unf
Material:
Steel flow control device
Material Specification:
Qq-s-764, type 303-cancelled federal specification single material response flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response

NSN 4820-00-024-4744

Check Valve - Page 2 of 2



Style	Designator:
-------	--------------------

Straight thru

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0