

View Online at <https://aerobasegroup.com/nsn/4820-00-025-9678>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

12 1st end

Maximum Operating Temp:

850.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outside Diameter:

14.000 inches 1st end

Face To Face Distance:

13.000 inches

Thickness:

2.062 inches 1st end

First Connection Face To Centerline Distance:

13.000 inches

Bolt Hole Diameter:

1.188 inches 1st end

Bolt Circle Diameter:

11.875 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

10.625 inches 1st end

Material:

Steel flow control device

Media For Which Designed:

Steam single response

Style Designator:

Angle

Test Data Document:

80064-dd692s4810-16 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Reference Number Differentiating Characteristics:

As differentiated by fig 133

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0