## NSN 4820-00-028-8066

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-028-8066 **Body Material:** Bronze, astm b61 First End Flange Outside Diameter: 7.000 inches **Outside Surface Treatment:** Any acceptable **Body Style:** Straight thru Stem Material: Nickel copper astm-b-164 or qq-n-288 Media For Which Designed: Water, fresh **First End Connection Type:** Plain face flange First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 0.500 inches First End Bolt Hole Quantity: First End Bolt Hole Diameter: 0.750 inches First End Bolt Circle Diameter: 5.500 inches Second End Relationship With First End: Identical **Seat Material:** Nickel copper astm-b-164 or qq-n-288 **Face To Face Distance:** 6.750 inches **Packing Material:** Rubber Flow Control Device: Disk, top guided Flow Control Device Material: Rubber **End Connection Quantity:** 

Renewable Seat Ring Type:

Threaded

## NSN 4820-00-028-8066

Fluid Pressure Regulating Valve - Page 2 of 2



| Regulation Type:  |
|---|
| 1st stage automatic, 2nd stage manual                           |
| Manual Control Method:  |
| Screw   |
| Valve Loading Method:   |
| Spring  |
| Remote Actuation Method:  |
| Bellows   |
| Maximum Inlet Pressure Rating:                                  |
| 150.0 pounds per square inch                                    |
| Filter:   |
| Not included  |
| First End Center To Center Distance Between Holes Along Length: |
| 5.500 inches  |
| End Application:  |
| Air conditioning system onboard 180 ft coast guard vessels      |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A21100  |
|   |