NSN 4820-00-028-8066

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-028-8066 **Body Material:** Bronze, astm b61 First End Flange Outside Diameter: 7.000 inches **Outside Surface Treatment:** Any acceptable **Body Style:** Straight thru Stem Material: Nickel copper astm-b-164 or qq-n-288 Media For Which Designed: Water, fresh **First End Connection Type:** Plain face flange First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 0.500 inches First End Bolt Hole Quantity: First End Bolt Hole Diameter: 0.750 inches First End Bolt Circle Diameter: 5.500 inches Second End Relationship With First End: Identical **Seat Material:** Nickel copper astm-b-164 or qq-n-288 **Face To Face Distance:** 6.750 inches **Packing Material:** Rubber Flow Control Device: Disk, top guided Flow Control Device Material: Rubber **End Connection Quantity:**

Renewable Seat Ring Type:

Threaded

NSN 4820-00-028-8066

Fluid Pressure Regulating Valve - Page 2 of 2



Regulation Type:
1st stage automatic, 2nd stage manual
Manual Control Method:
Screw
Valve Loading Method:
Spring
Remote Actuation Method:
Bellows
Maximum Inlet Pressure Rating:
150.0 pounds per square inch
Filter:
Not included
First End Center To Center Distance Between Holes Along Length:
5.500 inches
End Application:
Air conditioning system onboard 180 ft coast guard vessels
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A21100