## NSN 4820-00-031-7624

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-031-7624

Pipe Size Accommodated:					
0.250 inches all ends					
Thread Direction:					
Right-hand all ends					
Flow Control Device:					
Poppet					
Disk Loading Method:					
Spring					
Maximum Operating Temp:					
400.0 degrees fahrenheit single response					
End Application:					
Grumman aerospace a-10 aircraft					
Connection Style:					
Plain, optional en (pipe) all ends					
Valve Operation Method:					
Automatic					
Connection Type:					
Threaded internal pipe all ends					
Features Provided:					
Pressure tight outlet side					
Thready Qty Per Inch (tpi):					
18 all ends					
Adjustable Pressure Range:					
+10.0 to 50.0 pounds per square inch					
Maximum Operating Pressure:					
3100.0 pounds per square inch single response					
3100.0 pounds per square inch single response					
3100.0 pounds per square inch single response  Thread Size:					
3100.0 pounds per square inch single response  Thread Size:  0.250 inches all ends					
3100.0 pounds per square inch single response  Thread Size: 0.250 inches all ends  Opening Pressure Setting:					
3100.0 pounds per square inch single response  Thread Size: 0.250 inches all ends  Opening Pressure Setting: 35.0 pounds per square inch					
3100.0 pounds per square inch single response  Thread Size: 0.250 inches all ends  Opening Pressure Setting: 35.0 pounds per square inch  Material:					
3100.0 pounds per square inch single response  Thread Size: 0.250 inches all ends  Opening Pressure Setting: 35.0 pounds per square inch  Material:  Aluminum alloy					
3100.0 pounds per square inch single response  Thread Size: 0.250 inches all ends  Opening Pressure Setting: 35.0 pounds per square inch  Material:  Aluminum alloy  Media For Which Designed:					
3100.0 pounds per square inch single response  Thread Size: 0.250 inches all ends  Opening Pressure Setting: 35.0 pounds per square inch  Material:  Aluminum alloy  Media For Which Designed:  Fuel/oil, hydrocarbon single response					
3100.0 pounds per square inch single response  Thread Size: 0.250 inches all ends  Opening Pressure Setting: 35.0 pounds per square inch  Material:  Aluminum alloy  Media For Which Designed:  Fuel/oil, hydrocarbon single response  Surface Treatment:					
3100.0 pounds per square inch single response  Thread Size: 0.250 inches all ends  Opening Pressure Setting: 35.0 pounds per square inch  Material:  Aluminum alloy  Media For Which Designed:  Fuel/oil, hydrocarbon single response  Surface Treatment:  Anodize					
3100.0 pounds per square inch single response Thread Size: 0.250 inches all ends Opening Pressure Setting: 35.0 pounds per square inch Material: Aluminum alloy Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator:					
3100.0 pounds per square inch single response Thread Size: 0.250 inches all ends Opening Pressure Setting: 35.0 pounds per square inch Material: Aluminum alloy Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Err-090					
3100.0 pounds per square inch single response Thread Size: 0.250 inches all ends Opening Pressure Setting: 35.0 pounds per square inch Material: Aluminum alloy Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Err-090 Thread Series Designator:					

## NSN 4820-00-031-7624

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0