NSN 4820-00-035-6235

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-035-6235 **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand 1st end **Aperture Diameter:** 0.250 inches Flow Control Device: **Poppet Disk Loading Method:** Spring **Connection Style:** Gasket seal (boss) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 2nd end **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.250 inches 2nd end Material: Steel flow control device **Material Specification:** Mil-p-25732 military specification 2nd material response packing Media For Which Designed: Fuel/oil, hydrocarbon single response **Style Designator:** Straight thru **Thread Series Designator:** Unjf 2nd end Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 4820-00-035-6235

Restrictor Check Valve - Page 2 of 2



Fiig:

A530b0

Mil-std (military Standard):

Mil-p-25732 spec.