NSN 4820-00-035-6235

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-035-6235

Thread Class:

3b 2nd end

Thread Direction:

Right-hand 1st end

Aperture Diameter:

0.250 inches

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Connection Style:

Gasket seal (boss) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal boss 2nd end

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.438 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.250 inches 2nd end

Material:

Steel flow control device

Material Specification:

Mil-p-25732 military specification 2nd material response packing

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Straight thru

Thread Series Designator:

Unjf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4820-00-035-6235

Restrictor Check Valve - Page 2 of 2



Fiig: A530b0

Mil-std (military Standard):

Mil-p-25732 spec.