

View Online at <https://aerobasegroup.com/nsn/4820-00-043-2110>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Aperture Diameter:

0.014 inches

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

Flared (tube) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 2nd end

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.375 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Special Features:

Bulkhead fitting on first end

Material:

Steel comp 303 flow control device

Material Specification:

Qq-s-764, type 303-cancelled federal specification single material response flow control device

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification all treatment responses

Style Designator:

Straight thru

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-s-5002 spec.