## NSN 4820-00-043-3823

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-043-3823

Di a Oi a A a a a a a a la d
Pipe Size Accommodated:
0.750 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Connection Style:
Plain, optional en (pipe) 2nd end
Valve Operation Method:
Air
Connection Type:
Threaded internal pipe 2nd end
Thready Qty Per Inch (tpi):
14 2nd end
Adjustable Pressure Range:
+45.0/+55.0 pounds per square inch
Maximum Operating Pressure:
55.0 pounds per square inch single response
Thread Size:
0.750 inches 2nd end
Opening Pressure Setting:
50.0 pounds per square inch
Special Features:
Lox clean per a/f packaging k3655-00887, amend no. 1, 12 dec 1963
Material:
Copper alloy body
Media For Which Designed:
Oxygen, liquid single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
<b></b>
Demilitarization:

No

## NSN 4820-00-043-3823

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0