

View Online at <https://aerobasegroup.com/nsn/4820-00-045-3425>

Thread Class:

3a all ends

Thread Direction:

Right-hand 1st end

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

Flared (tube) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded external tube all ends

Thready Qty Per Inch (tpi):

18 all ends

Maximum Operating Pressure:

60.0 pounds per square inch single response

Thread Size:

0.562 inches all ends

Seat Angle:

37.0 degrees all ends

Outside Diameter Tube Accommodated:

0.375 inches all ends

Special Features:

W/detents under handle to hold valve in closed position, 2nd end w/bulkhead type end per ms3367-6, body valve seats spring loaded

Material:

Steel comp 303 stem

Material Specification:

Qq-a-591, alloy380 federal specification single material response body

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.