## NSN 4820-00-052-4106

Safety Relief Valve - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/4820-00-052-4106

Pipe Size Accommodated:
0.125 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
250.0 degrees fahrenheit 2nd response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Adjustable Pressure Range:
+0.5 to 140.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.125 inches 1st end
Opening Pressure Setting:
0.5 pounds per square inch
Material:
Steel comp 302 flow control device
Material Specification:
Fedstd66, aisi302/sae30302 federal standard single material response flow control device
Media For Which Designed:
Hydrogen 5th response
Surface Treatment:
Anodize
Style Designator:
Straight thru
Thread Series Designator:
Npt 1st end
Furnished Items And Quantity:
1 deflector cap
Shelf Life:

## NSN 4820-00-052-4106

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0