## NSN 4820-00-052-6567

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-052-6567 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit 2nd response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends **Maximum Operating Pressure:** 60.0 pounds per square inch single response **Thread Size:** 1.625 inches all ends Seat Angle: 37.0 degrees 1st end **Outside Diameter Tube Accommodated:** 1.250 inches all ends Material: Aluminum alloy seat Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Un all ends

Shelf Life:

N/a

## NSN 4820-00-052-6567

Check Valve - Page 2 of 2



 :4	$\sim$	Measure:
 nit	( )T	MESCIILE.

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.