## NSN 4820-00-053-4546

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-053-4546 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 1.2 gallons per minute **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends **Opening Pressure Setting:** 1285.0 pounds per square inch **Special Features:** Free reverse flow Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base single response Straight through note: to be used for valve bodies of one section only.

**Surface Treatment:** Anodize **Style Designator: Thread Series Designator:** Unjf all ends Shelf Life: N/a **Unit Of Measure:** 

## NSN 4820-00-053-4546

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0