## NSN 4820-00-053-4565

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-053-4565 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 3.5 gallons per minute **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 1st end Thready Qty Per Inch (tpi): 18 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.562 inches 1st end **Opening Pressure Setting:** 1100.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.375 inches 1st end Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Style Designator:** Straight thru **Thread Series Designator:** Unjf 1st end Shelf Life:

Unit Of Measure:

N/a

## NSN 4820-00-053-4565

Safety Relief Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A046b0