NSN 4820-00-054-3782

Lift-check Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-054-3782

Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 1st end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Mounting Position:
Horizontal or vertical
Valve Size:
1.000 inches
Criticality Code Justification:
Zzzy
Outside Diameter:
4.875 inches 1st end
Face To Face Distance:
3.000 inches
Thickness:
1.250 inches 1st end
Bolt Hole Diameter:
0.687 inches 1st end
Bolt Circle Diameter:
3.500 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
2.000 inches 1st end
Material:
Steel comp 304 seat
Style Designator:
Straight through flanged ends

NSN 4820-00-054-3782

Lift-check Valve - Page 2 of 2



Reference Number Differentiating Characteristics:

Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0