NSN 4820-00-054-3790

Lift-check Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Disk Loading Method:

Bolt Hole Quantity:

Valve Operation Method:

Bonnet Type: Inside spring

Threaded

Spring

8 1st end

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-054-3790

Automatic
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Mounting Position:
Horizontal or vertical
Valve Size:
3.000 inches
Criticality Code Justification:
Zzzy
Outside Diameter:
8.250 inches 1st end
Face To Face Distance:
4.500 inches
Thickness:
2.250 inches 1st end
Bolt Hole Diameter:
0.875 inches 1st end
Bolt Circle Diameter:
6.625 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
5.000 inches 1st end
Style Designator:
Straight through flanged ends
Reference Number Differentiating Characteristics:
Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items

NSN 4820-00-054-3790

Lift-check Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0