NSN 4820-00-055-5114

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-055-5114

Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
3.5 gallons per minute
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 all ends
Maximum Operating Pressure:
275.0 pounds per square inch single response
Thread Size:
0.562 inches all ends
Opening Pressure Setting:
240.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.375 inches all ends
Material:
Stainless steel flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unf all ends

NSN 4820-00-055-5114

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.

