

View Online at <https://aerobasegroup.com/nsn/4820-00-055-9697>

Flow Control Device:

Plug

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 1st end

Maximum Operating Temp:

500.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

5.000 inches 1st end

Thickness:

0.562 inches 1st end

First Connection Face To Centerline Distance:

3.250 inches

Bolt Hole Diameter:

0.625 inches 1st end

Second Connection Face To Centerline Distance:

3.250 inches

Bolt Circle Diameter:

3.875 inches 1st end

Flange Face Design:

Plain 1st end

Special Features:

Semi-plug, top guided

Material:

Steel seat

Material Specification:

Astm a351, gr cf8m assn standard single material response seat

Media For Which Designed:

Water-oil-gas single response

Surface Treatment:

Passivate

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0