## NSN 4820-00-056-2521

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-056-2521

Body		

Aluminum alloy, qq-a-200/3, alloy 2024, t4

**Outside Surface Treatment:** 

Anodized, mil-a-8625, type 2

**Body Style:** 

Angle

Media For Which Designed:

Air and nitrogen, gaseous

**First End Connection Type:** 

Threaded internal boss

First End Style Designator:

Gasket seal

First End Thread Size And Series/type Designator:

0.438-20 unjf

**First End Thread Class:** 

За

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Identical

**Packing Material:** 

Rubber, synthetic, mil-p-5516, class b

**Flow Control Device:** 

Disk

**End Connection Quantity:** 

End 2

**Outlet Pressure Range:** 

+980.0/+1020.0 pounds per square inch

**Regulation Type:** 

Automatic single stage

Valve Loading Method:

Bellows

**Maximum Inlet Pressure Rating:** 

3000.0 pounds per square inch

**Outlet Pressure Setting:** 

1000.0 pounds per square inch

**Outlet Pressure Accuracy Rating:** 

20.000 pounds per square inch

Filter:

Not included

**Tempurature Rating:** 

55.0 degrees celsius

## NSN 4820-00-056-2521

Fluid Pressure Regulating Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A21100