NSN 4820-00-056-7677

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-056-7677

Pipe Size Accommodated:
0.750 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
68.0 cubic feet per minute
Maximum Operating Temp:
450.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Manual
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Maximum Operating Pressure:
300.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Opening Pressure Setting:
30.0 pounds per square inch
Material:
Stainless steel stem
Media For Which Designed:
Gas, natural 3rd response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-056-7677

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0