NSN 4820-00-057-3494

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-057-3494

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Ball
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
8.7 pounds per hour
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Features Provided:
Valve stem lock shield and bonnet packing
Thready Qty Per Inch (tpi):
18 1st end
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
90.0 pounds per square inch
Material:
Stainless steel
Media For Which Designed:
Air single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

NSN 4820-00-057-3494

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0