NSN 4820-00-058-1677

Globe Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Renewable Seat Ring Type:

Disk

Bolted

Threaded



View Online at https://aerobasegroup.com/nsn/4820-00-058-1677

| Bolt Hole Quantity: |
|---|
| 8 1st end |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes 1st end |
| Connection Type: |
| Flange 1st end |
| Features Provided: |
| Bonnet packing |
| Maximum Operating Pressure: |
| 123.0 pounds per square inch single response |
| Outside Diameter: |
| 9.000 inches 1st end |
| Face To Face Distance: |
| 11.500 inches |
| Thickness: |
| 0.938 inches 1st end |
| Bolt Hole Diameter: |
| 0.750 inches 1st end |
| Bolt Circle Diameter: |
| 7.500 inches 1st end |
| Flange Face Design: |
| Plain 1st end |
| Special Features: |
| 4.000 in. Nom pipe size |
| Material: |
| Iron cast body |
| Media For Which Designed: |
| Steam single response |
| Style Designator: |
| Straight through flanged ends |
| Reference Number Differentiating Characteristics: |
| As differentiated by special features |
| |
| |

NSN 4820-00-058-1677

Globe Valve - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0