NSN 4820-00-059-4933

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-059-4933

Thread Class:

Thread Class: 2b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 400.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Manual **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side Adjustable Pressure Range: +235.0/+450.0 pounds per square inch **Maximum Operating Pressure:** 2200.0 pounds per square inch single response **Thread Size:** 0.562 inches all ends **Opening Pressure Setting:** 360.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.375 inches all ends Material: Stainless steel seat Media For Which Designed: Water-oil-gas single response **Surface Treatment: Passivate Style Designator:** Angle **Thread Series Designator:** Unjf all ends Shelf Life:

Unit Of Measure:

N/a

NSN 4820-00-059-4933

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0