## NSN 4820-00-059-4933

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-059-4933

Thread Class:
2b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) all ends
Valve Operation Method:
Manual
Connection Type:
Threaded internal boss all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+235.0/+450.0 pounds per square inch
Maximum Operating Pressure:
2200.0 pounds per square inch single response
Thread Size:
0.562 inches all ends
Opening Pressure Setting:
360.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.375 inches all ends
Material:
Stainless steel seat
Media For Which Designed:
Water-oil-gas single response
Surface Treatment:
Passivate
Style Designator:
Angle
Thread Series Designator:
Unjf all ends
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 4820-00-059-4933

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

