## NSN 4820-00-060-3195

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-060-3195

View Online at https://aerobasegroup.com/nsn/4820-00-060-3195
Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Features Provided:
Valve stem lock shield
Thready Qty Per Inch (tpi):
12 all ends
Maximum Operating Pressure:
125.0 pounds per square inch single response
Thread Size:
1.062 inches all ends
Opening Pressure Setting:
90.0 pounds per square inch
Material:
Plastic polytetrafluoroethylene flow control device and aluminum alloy flow control device
Media For Which Designed:
Water-oil-gas single response
Surface Treatment:
Anodize
Style Designator:
Thread Series Designator:
Un all ends

## NSN 4820-00-060-3195

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

