NSN 4820-00-060-3195

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-060-3195 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Bonnet Type:** Inside screw **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring Renewable Seat Ring Type: Pressed-in **Maximum Operating Temp:** 225.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Valve stem lock shield Thready Qty Per Inch (tpi): 12 all ends **Maximum Operating Pressure:** 125.0 pounds per square inch single response **Thread Size:** 1.062 inches all ends **Opening Pressure Setting:** 90.0 pounds per square inch Material: Plastic polytetrafluoroethylene flow control device and aluminum alloy flow control device Media For Which Designed: Water-oil-gas single response **Surface Treatment:** Anodize **Style Designator:** Angle

Thread Series Designator: Un all ends

NSN 4820-00-060-3195

Safety Relief Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0