

View Online at <https://aerobasegroup.com/nsn/4820-00-060-3203>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Maximum Operating Temp:

275.0 degrees fahrenheit single response

End Application:

Acft, type f-4; t.O. 1f-4c-4-3, fig 104, ind 18

Connection Style:

Flared (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

12 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Special Features:

Outlet end bulkhead per ms33657, angle of valve is 45 degrees

Material:

Stainless steel

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Surface Treatment:

Passivate

Style Designator:

Angle

Supplementary Features:

Nha ref no. 53-69724 ()

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A530b0